# Gable-Roof Sunroom

A glass room with a gable (herringbone) roof for a lofty, conservatory feel.



## KEY PERFORMANCE

| | |
|---|---|
| Supply status | On request for projects |
| Category | Skylights & sunrooms |
| Wind load resistance (factory test) | 5.0 kPa |

## CONSTRUCTION

| | |
|---|---|
| Aluminium | 6063-T5 aluminium alloy |
| Finish | Fluorocarbon Coating, Heat transfer printed wood grain |
| Finish | Metallic Coffee, Metallic Gray, White, Customized RAL colors |
| Glazing | Roof 5 + 0. 76 pvb+ 5 mm laminated toughened glass |
| Note | Aluminum profiles in the load-bearing part are 3.0 mm thickness. |
| Note | No connection marks on the surface, perfect component structure. |
| Note | The roof can be equipped with an electric skylght ventilation system. |
| Note | Bi-fold door, sliding doorswing door, windows can be fixed on sides. |

## COMPLIANCE & SUPPLY

| | |
|---|---|
| Standards | AS 2047 windows and doors; glass to AS 1288; wind rating to the site class (AS 4055); BAL-rated glazing on request (AS 3959) |
| Energy data | Frame and glass U-value and SHGC supplied per series for NatHERS, BASIX or NCC energy reports |
| Supply | Made to measure to your schedule, shop drawings for sign-off, labelled by opening, delivered to site Australia-wide. Supply only. |

Figures are the factory's published test results for the series and depend on size, glass and configuration. Final values for your windows are confirmed on the shop drawings and the AS 2047 test report supplied with the quote. Section drawings in DWG are available on request.